



specialty lubricants



*Quality is in our nature*

## Eurol Grease CS-2/101

Lubrication grease / anti corrosion agent

### Description:

Eurol Grease CS-2 / 101 with Eurol SYNGIS Technology is a high performance lubricating grease developed for extreme situations in e.g. the paper, cement and steel industry and heavy equipment in offshore and shipping.

### Instructions for use:

- Clean the system thoroughly with Eurol Switt Clean 110 Spray
- Suitable for automatic lubrication systems

Eurol Grease CS-2 / 101 is suitable for lubrication of:

- Open and closed bearings
- Cables and chains
- Autoclaves
- Steam valves
- Agricultural and fishing equipment
- Equipment working in extreme environments like (salt) water and high temperatures

### Eurol Grease CS-2/101 has the following characteristics:

- Excellent anti wear and EP properties
- Extreme protection against corrosion
- Shear stable
- Excellent water resistancy
- Resistant to shock loads
- Very good thermal and oxidation stability
- Less oil bleeding, so very suitable for automatic lubrication systems
- Economical in use

### Physical properties:

Colour	Brown		
NLGI consistency	2		ASTM D 217
Thickener type	Calcium Sulfonate		
Density at 20°C	1.02	kg/l	ASTM D 1298
Base oil viscosity	300	cSt	ASTM D 445
Base Oil Type	Mineral		
Operating temperature	-30 - 140	°C	

Greases - S005110  
Version 1.0, 21-08-2015

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com