



specialty lubricants



*Quality is in our nature*

## Eurol Grease EG-0/101

Lubrication grease for use at exceptionally high loads

### Description:

Eurol Grease EG-0/101 with Eurol SYNGIS Technology is a (NLGI 0) lubricating grease developed for extreme applications combined with exceptional high loads. Especially useful in e.g. the paper, cement and steel industry or for heavy equipment in offshore and shipping.

Eurol Grease EG-0/101 is suitable for lubrication of:

- Open bearings
- Open gears
- Gear / worm transmissions

### Instructions for use:

- Remove old grease residue from the system or lubrication point as much as possible and clean thoroughly
- Suitable for automatic lubrication systems

### Eurol Grease EG-0/101 has the following characteristics:

- Very resistant against water wash out and spray off
- Extreme protection against corrosion
- Resistant to shock loads
- Oxidation- and thermal stable
- Superior mechanical stability
- Almost no oil bleeding so very suitable for automatic lubrication systems
- Economical in use

### Physical properties:

|                       |                 |      |             |
|-----------------------|-----------------|------|-------------|
| Colour                | dark brown      |      |             |
| NLGI consistency      | 0               |      | ASTM D 217  |
| Thickener type        | Calcium Complex |      |             |
| Density at 20°C       | 1.01            | kg/l | ASTM D 1298 |
| Base oil viscosity    | 700             | cSt  | ASTM D 445  |
| Base Oil Type         | Mineral         |      |             |
| Operating temperature | -25 - 150       | °C   |             |
| 4-ball weld load      | 750             | kg   |             |

Greases - S005130  
Version 1.0, 11-02-2016

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com