



specialty lubricants



Quality is in our nature

Eurol Swift Clean 400

Very powerful cleaner and descaler

Description:

Eurol Swift Clean 400 is a very powerful, highly concentrated, water dilutable acid cleaner for removing pollutants like calc and rust from machinery, plumbing, tiles and hard surfaces. Suitable for industrial use, as well as heavy machinery, hospitals, swimming pools and wellness; anywhere where rust, urine, limescale, soap residue, cement and other construction remains are a problem. Suitable for cleaning floors, sanitary ware, boilers, tiles, glass, stone, concrete, plastics, iron, steel and stainless steel.

Recommended dilution in water:

Fly rust 1:1 up to 1:3

Urine scale 1:3 up to 1:5

Steel surfaces 1:1 up to 1:10

Concrete / cement veil 1:5 up to 1:20

Oven cleaning 1:10 up to 1:20

Floor and wall tires 1:10 up to 1:100

Instructions for use:

- Remove as much pollution as possible with a cloth, spatula, rag or brush.
- Dilute the cleaner according to the mixing ratio. Allow to soak and rinse with ample water.
- Never mix with different cleaners.
- Not suited for cleaning marble, limestone and galvanised parts such as gutters.
- First test on an inconspicuous surface. Never allow the cleaner to dry.
- After removing rust, rinse with ample water and treat the surface with rust-repellent Eurol PL Lube Spray.

Eurol Swift Clean 400 has the following characteristics:

- Very effective cleaning capability
- Biodegradable
- Packaging is recyclable HDPE
- Removes heavy pollution
- Highly dilutable, costeffective
- Removes rust and calcareous deposits

Physical properties:

Colour	Colourless	
Density at 20°C	1.41 kg/l	ASTM D 1298
pH	1	

Version 1.0, 19-06-2019

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com