



specialty lubricants



Quality is in our nature

Eurol Lube PL

“Dry” multi-functional lubricant reinforced with SYNGIS Technology

Description:

Eurol Lube PL is a “dry” lubricant with Eurol SYNGIS Technology. Eurol Lube PL has been developed for non-drip, “dry”, clean and durable lubrication of many applications where excellent creeping, penetration and anti-corrosion properties are required. It displaces moisture, resists water and loosens corroded parts. Thanks to the “dry” lubrication properties dirt and sand are not being picked up.

Eurol Lube PL is especially suitable for:

- All open lubrication points like e.g. joints, bearings and hinges
- Cables and conveyors

Instructions for use:

- Clean and degrease parts thoroughly
- Apply a thin film
- Allow the product to penetrate and dry
- Remove excess product with a clean cloth
- For more demanding applications, Eurol PL-S Lube with a higher concentration SYNGIS Technology is available

Eurol Lube PL has the following characteristics:

- Excellent anti wear properties
- Excellent protection against corrosion
- Excellent cleaning action
- Outstanding water repellency
- Very good creeping and penetration properties
- Loosens corroded parts
- Gives a thin and “dry” protective lubrication film
- Does not attract dirt or sand
- Very low friction coefficient
- Reduces energy consumption
- Economical in use

Physical properties:

Colour	Brown		
Density at 20°C	0.872	kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	32	cSt	ASTM D 445
Flash point	60	°C	ASTM D 93
Operating temperature	-20 - 140	°C	

Industrial oils - Semi-synthetic - S009101
Version 1.0, 15-09-2017

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurolspecialty.com